

Product Specifications for 403D-07



Power Rating

Maximum Power	15.3 kW
Maximum Torque	50.4 Nm @ 2400 rpm
Rated Speed	2800-3600 rpm
Minimum Power	12.2 kW

Emission Standards

Emissions	EU Stage IIIA/U.S. EPA Tier 4 Interim equivalent
------------------	--

General

Number of Cylinders	3 inline
Cycle	4 stroke
Bore	67 mm
Stroke	72 mm
Displacement	0.76 l
Compression Ratio	23.5:1
Aspiration	Naturally aspirated
Combustion System	Indirect injection
Rotation from Flywheel End	Anti-clockwise
Aftertreatment	-
Cooling System	Liquid

Engine Dimensions*

Length	480 mm
Width	371 mm
Height	528 mm
Dry Weight	71 kg

Disclaimer

Note 1

*Final dimensions dependent on selected options

403D-07 Standard Equipment

Cooling System

Coolant temperature switch
Cooling fan

Electrical and Electronics

Alternator 12V, 14 amps
Starter motor 12V, 0.8-1.2 kW
Electronic Shut Off Solenoid (ESOS)
Glow plug starting aid

Flywheel and Flywheel Housing

Flywheel housing SAE5
Flywheel SAE 6 1/2

Fuel System

Fuel injection pump
Spin on fuel filter

General

Gradeability 35° continuous

Oil System

Closed circuit breather
Lubricating oil pressure switch
Spin on lubricating oil filter
Dipstick options available