

# Product Specifications For C2.8



## Power Rating

Maximum Power	74 hp
Maximum Torque	280 lb-ft @ 1360 rpm
Rated Speed	2200 - 2400 rpm
Minimum Power	67 hp

## Emission Standards

Emissions	U.S. EPA & CARB Tier 4 Final, EU Stage V
-----------	--

## General

Engine Configuration	In-Line 4
Bore	3.5 in
Stroke	4.3 in
Displacement	171 in <sup>3</sup>
Compression Ratio	17.0:1
Aspiration	Turbocharged (T) and Turbocharged-Aftercooled (TA)
Combustion System	Direct Injection
Rotation from Flywheel End	Counterclockwise
Aftertreatment	DOC+DPF

## Engine Dimensions - Approximate

Length	24.9 in
--------	---------

<b>Width</b>	22.4 in
<b>Height</b>	30.9 in
<b>Weight - Net Dry - Basic Operating Engine Without Optional Attachments</b>	750 lb

## C2.8 Standard Equipment

### Air Inlet System

Induction manifolds  
 Exhaust manifolds  
 Engine-mounted aftertreatment

### Control System

Starter motor (12V)  
 Alternator (12V)  
 Electronic Control Unit (chassis mounted)  
 Engine control sensors and robust wiring harness  
 Data interface via CANbus J1939

### Flywheels And Flywheel Housing

Flywheel housings – SAE 3 or SAE 4  
 Choice of flywheel to match industry common hydraulic pumps and transmissions  
 Side PTO with SAE A or SAE B interface

### Fuel System

Fuel filter – preconnected but chassis mounted  
 With water sensor

### Lube System

Lubricating oil filters  
 High incline oil pan – 35° continuous in all directions

### General

Cold start capability to -20° C (-4° F) with standard equipment  
 Paint: Caterpillar yellow, with optional colors available at request

## U.S. EPA Tier 4 Final, Proposed EU Stage V Aftertreatment/ Clean Emissions

### Control Equipment

Diesel Oxidation Catalyst (DOC) (Tier 4 Final and Stage V)  
 Diesel Particulate Filter (DPF) (Stage V)